

The MGS-I is a *Patented* Red/GreenReflex Dot Sight specifically designed and built for the .50 Caliber, M60E6/E4 /M240 /M-134 Minigun (7.62mm) Machine Guns and MK19 40mm Automatic Grenade launcher which are widely used in the armed forces.

- 3rd Generation Machine Gun sight offering a very large field of view designed with an unequalled 120 x 70 mm lens (Medium Lens available) that provides rapid acquisition and tracking of stationary and moving targets
- Provides pinpoint accuracy which ensures every round is on target suppressing enemy fire faster, reducing collateral damage and reducing drastically ammunition consumption
- Patented removable LED light source module with a stadia line style reticle that improves accuracy by eliminating the need for sighting guesswork
- Without a manual BDC dial, gunners can keep both hands-on Spade Grip and their eyes on target at all time

Machine Gun Sight Features

- Universal sight design—one sight for all machine guns
- **Modular Design**—allows to configure the sight to meet a specific mission criteria
- **Easy to maintain** / repair / upgrade
- **Available with Red or Green LED light source** for better visibility in high sunlight
- **Auto or Manual** Brightness control
- **MGS-1** is available for the following standard calibers: 7.62mm 12.7mm &. 40mm (Other calibers upon request)
- Easily upgrade with a video camera system for remote aiming
- **Optional**: 3x magnifier and Honeycomb













Machine Gun Sight Specifications

CALIBERS

MGS1-M1X & MGS1-L1X: 12.7 mm (0.50 Cal)

DIMENSIONS [L XW X H]

MGS1-M1X: ~ 8.6 x 4.7 x 4.5 in (220 x 120 x 115 mm) MGS1-L1X: ~9.4 x 6 x 5.1 in (240 x 150 x 130mm)

WEIGHT

MGS1-M1X: ~3 Lbs (~1.4 kg) | MGS1-L1X: ~4.5Lbs (~2 kg)

LENS SIZE

MGS1-M1X: ~3.4 x 2 in (88x 55 mm) | MGS1-L1X: 4.7 x 2.8 in (120 x 70mm)

TOTAL FIELD OF VIEW

MGS1-M1X & MGS1-L1X:: ~80m at 200m (>25 degrees)

AZIMUTH/ELEVATION ADJ.

MGS1-M1X & MGS1-L1X: ~0.5 MOA/click

EYE RELIEF

MGS1-M1X & MGS1-L1X: Unlimited

RED OR GREEN DOT SIZE

MGS1-M1X & MGS1-L1X: Dot = 3 MOA and Circle = 35 MOA

TORQUE LIMIT LOCK (TLL)

MGS1-M1X & MGS1-L1X: >3.0 Nm

LED COLORS

MGS1-M1X & MGS1-L1X: Red and Green selectable

TRAJECTORY RANGES

MGS1-M1X & MGS1-L1X: 200.400.600.800.1000.1200.1400.1600 & 1800

BRIGHTNESS ADJUSTMENTS

MGS1-M1X & V: 8 daylight & 3 Night Vision settings

MAGNIFICATION-OPTIONS

MGS1-M1X & MGS1-L1X:: 3x, 5x, or 3-8x Variable

POWER SUPPLY

MGS1-M1X & MGS1-L1X: 1 type CR 123 3V lithium

BATTERY LIFE ~1000+ HR

MGS1-M1X & MGS1-L1X: ~1000 hr

MOUNTING

MGS1-M1X & MGS1-L1X: MIL-STD-1913 rail (3 rails)

OPERATIONAL TEMP

MGS1-M1X & MGS1-L1X: -41 degrees C to +71 degrees C





